

Specifications for Sonic Loudspeaker Systems

model	woofer	impedance	RMS handling	response	woofer v.c.	driver v.c.	HF dispersion	sensitivity	dimensions	weight
Full Range Series										
TM15	standard	8 ohms	250 watts RMS	52-19khz	2.5"	1"	90x40	103db	26"x19"x15"	42 lbs.
T12	standard	8 ohms	200 watts RMS	60-19khz	2"	1"	90x40	101db	24"x18"x15"	40 lbs.
T15	standard	8 ohms	250 watts RMS	55-19khz	2.5"	1"	90x40	102db	28"x20"x16"	48 lbs.
T15	SCF600	8 ohms	650 watts RMS	52-19khz	4"	1"	90x40	101db	28"x20"x16"	59 lbs.
T153	standard	8 ohms	250 watts RMS	48-19khz	2.5"	2"	90x40	102db	36"x21"x20"	83 lbs.
T153	SCF600	8 ohms	650 watts RMS	44-19khz	4"	2"	90x40	101db	36"x21"x20"	93 lbs.
T215FR	SCF600	4 ohms	1200 watts RMS	43-19khz	4"	2"	90x40	104db	48"x21"x20"	145 lbs.
Two Inch Horn Enclosures										
T153-2	SCF600	8 ohms	700 watts RMS	43-19.5khz	4"	3"	80x40	102db	36"x21"x20"	96 lbs.
T215FR-2	SCF600	4 ohms	1200 watts RMS	45-19.5khz	4"	3"	80x40	104db	48"x21"x20"	148 lbs.
LTX Series										
LTX10	standard	8 ohms	100 watts RMS	65-19khz	1.5"	dual piezo	90x40	100db	20"x13"x11"	24 lbs.
LTX10M	standard	8 ohms	100 watts RMS	65-19khz	1.5"	dual piezo	90x40	100db	14"x13"x22"	21 lbs.
LTX12	standard	8 ohms	150 watts RMS	55-19khz	1.5"	1"	90x40	101db	22"x17"x15"	37 lbs.
LTX12M	standard	8 ohms	150 watts RMS	55-19khz	1.5"	1"	90x40	101db	16"x17"x24"	28 lbs.
LTX15	standard	8 ohms	250 watts RMS	52-19khz	2.5"	1"	90x40	102db	26"x19"x16"	45 lbs.
Monitors										
D12	standard	8 ohms	200 watts RMS	55-19khz	2"	1"	90x40	101db	15"x24"x19"	39 lbs.
D15	standard	8 ohms	250 watts RMS	54-19khz	2.5"	1"	90x40	101db	15"x26"x20"	45 lbs.
M15	SCF600	8 ohms	650 watts RMS	52-19khz	4"	1"	90x40	101db	22"x20"x29"	74 lbs.
MSM	standard	8 ohms	100 watts RMS	75-18khz	1"	n/a	n/a	93db	8"x13"x 7"	8 lbs.
DJX Series										
DJX215	standard	4 ohms	450 watts RMS	40-19khz	2.5"	1"	90x40	103db	44"x20"x16"	79 lbs.
DJX183	SCF800	8 ohms	800 watts RMS	40-18khz	4"	2"	90x40	102db	40"x25"x24"	126 lbs.
Sub Enclosures										
18E	SCF800	8 ohms	800 watts RMS	35-.25khz	4"	n/a	n/a	102db	36"x24"x36"	133 lbs.
18W	SCF800	8 ohms	800 watts RMS	38-.35khz	4"	n/a	n/a	102db	24"x48"x30"	153 lbs.
T118 Sub	SCF800	8 ohms	800 watts RMS	43-7khz	4"	n/a	n/a	102db	36"x24"x24"	95 lbs.
T215 Sub	SCF600	4 ohms	1200 watts RMS	45-7khz	4"	n/a	n/a	101db	36"x24"x24"	112 lbs.
R218 Sub	SCF800	4 ohms	1600 watts RMS	40-7khz	4"	n/a	n/a	102db	24"x48"x30"	174 lbs.
118 Scoop	SCF800	8 ohms	800 watts RMS	40-.5khz	4"	n/a	n/a	101db	48"x24"x30"	154 lbs.